



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900
708-534-3957 (FAX)

Technical Data Sheet

Product series **GCT**
Product description **Glass cloth tape**

General Description and Typical Applications

Tightly woven, high tensile strength fiberglass cloth tape has a high thermal rating, is flame retardant, abrasion and edge tear resistant, conformable and provides solvent resistance. This glass cloth tape is an excellent choice for electrical and mechanical applications where chemical resistance properties of PTFE are not required. Also suitable for high temperature and thick film-build powder coating masking requirements.

Product Construction

Color(s) **White**
Total thickness **7 mils**
Backing thickness **0.005**
Adhesive thickness **0.002**
Adhesive type **Silicone**

Product Physical Characteristics

Maximum temperature **500°F**
Minimum temperature **-100°F**
Adhesion to steel **30 oz./in. width**
Tensile strength **160 lbs./sq. inch**
Elongation at break **Not available**
Liner thickness (if applicable) **Not applicable**

Storage, Shelf Life and additional information

Store at temperatures not to exceed 70°F, with relative humidity less than 50%, and away from direct sources of heat and sunlight. For optimum shelf life, store PSA tapes in an air-conditioned environment or cold storage room below 50°F (Please store tape for at least 12 – 24 hours, at room temperature, before use).

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.