



1201 Teal Avenue, Suite A  
Peotone, IL 60468  
866-534-3900 (Toll-Free)  
708-534-3900  
708-534-3957 (FAX)

## ***Technical Data Sheet***

Product series                      **PVC6**  
Product description                **Adhesive vinyl tape**

### **General Description and Typical Applications**

Colored, stabilized, plasticized, soft polyvinylchloride film (SPVC) for floor, lane and aisle marking as well as masking operations. Used in HVAC industry to wrap line sets, seam Rubatex and Armatex and insulate air ducts and underground pipes. UV resistant, flexible and usable in moist & humid conditions.

### **Product Construction**

Color(s)                                **Black, white, yellow, green, red, dark blue**  
Total thickness                      **5.25 mils**  
Backing thickness                  **4.0 mils**  
Adhesive thickness                **1.25 mils**  
Adhesive type                        **Rubber-based**

### **Product Physical Characteristics**

Maximum temperture                **140°F**  
Minimum temperature               **20°F**  
Adhesion to steel                    **20 oz/in width**  
Tensile strength                      **13 lbs/in width**  
Elongation                             **200%**

### **Storage, Shelf Life and additional information**

Store under normal conditions of 60° to 80°F and 40 to 60% relative humidity  
For best performance, use this product within 12 months from date of sale

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.