



1201 Teal Avenue, Suite A  
Peotone, IL 60468  
866-534-3900 (Toll-Free)  
708-534-3900  
708-534-3957 (FAX)

## ***Technical Data Sheet***

Product series                   **VGT215**  
Product description           **Green polyester tape**

### **General Description and Typical Applications**

Heavy duty 2 mils thick polyester film coated with a high temperature fully cured silicone adhesive. The adhesive is designed to be fully stable at elevated operating temperatures. The adhesion of the silicone system allows for the tape to be die cut in small sizes offering good quick-stick. Removes cleanly leaving a well defined mask area.

### **Product Construction**

Color(s)                           **Green**  
Total thickness                 **3.4 mils**  
Backing thickness              **2.0 mils**  
Adhesive thickness            **1.4 mils**  
Adhesive type                  **Silicone**

### **Product Physical Characteristics**

Maximum temperature         **400°F**  
Adhesion to steel              **34 oz./in. width**  
Tensile strength                **30 lbs./in. width**  
Liner thickness (if applicable) **Not applicable**

### **Storage, Shelf Life and additional information**

Store under normal conditions of 70°F and 50% relative humidity.  
For best performance, use this product within 12 months from date of sale.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believe this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.