



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900
708-534-3957 (FAX)

Technical Data Sheet

Product series **VT304L**
Product description **Stainless steel tape**

General Description and Typical Applications

Non-corrosive, non-magnetic tape for use in marine, food processing and nuclear applications. Also useful for decorative applications. It employs a 304 alloy of stainless steel substrate with an acrylic adhesive system, wound on a paper release liner. Bonds well to metals and other non-porous surfaces. Can be applied in both low and higher temperature environments.

Product Construction

Color(s)	Steel
Thickness w/o liner	3.8 mils +/- 10%
Backing thickness	2 mils
Adhesive type	Acrylic
Interliner	Polycoated Kraft

Product Physical Characteristics

Maximum temperature	250°F
Minimum temperature	-40°F
Tensile strength	150 lbs/in of width
Peel Strength	45 oz./in.
Elongation at break	1%
Color	Silver

Storage, Shelf Life and additional information

Store under normal conditions of 60° to 80°F and 40 to 60% relative humidity
Two years shelf life.

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.