



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900
708-534-3957 (FAX)

Technical Data Sheet

Product series **VT468**
Product description **Double-sided banner tape**

General Description and Typical Applications

Double-faced 1 mil polyester film tape coated on both sides with a high tack and aggressive acrylic adhesive system for superior bonding. Designed as a PVC banner hem tape. Works in a wide range of temperatures and environments. Can also be used as a high temperature splicing tape. A non-stock single-sided version of this banner tape is also available.

Product Construction

Color(s) **White**
Total thickness **6.5 mils**
Backing thickness **0.5 mils**
Adhesive thickness **3.0 mils** per side
Adhesive type **Acrylic**

Product Physical Characteristics

Maximum temperature **275°F**
Peel Adhesion **130 oz/in.**
Tensile strength **Not available**
Elongation at break **Not available**
Liner thickness (if applicable) **Not available**

Storage, Shelf Life and additional information

Store under normal conditions at 70°F and 50% relative humidity
For best performance, use this product within 12 months from date of sale

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believes this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.