



1201 Teal Avenue, Suite A
Peotone, IL 60468
866-534-3900 (Toll-Free)
708-534-3900
708-534-3957 (FAX)

Technical Data Sheet

Product series **VT929**
Product description **Single-sided polyester tape**

General Description and Typical Applications

Single-sided adhesive polyester tape designed for surface protection and chemical etching. Has superior adhesion to radiation cured surfaces. Also a silicone splicing tape that offers a low profile. Bonds quickly and permanently to silicone surfaces. Has high temperature capability, and the silicone-based adhesive system resists oozing and flow.

Product Construction

Color(s) **Red, blue, clear**
Total thickness **2.4 mils**
Backing thickness **1.0 mil**
Adhesive thickness **1.4 mils**
Adhesive type **Silicone**

Product Physical Characteristics

Maximum temperature **385°F**
Minimum temperature **-65°F**
Adhesion to steel **36 oz./in. width**
Tensile strength **Not available**
Elongation at break **Not available**
Liner thickness (if applicable) **Not applicable**

Storage, Shelf Life and additional information

Store under normal conditions of 60° to 80°F and 40 to 60% relative humidity
For best performance, use this product within 12 months from date of sale

The technical information and other statements contained on this sheet are derived from vendor-supplied information. Viadon believe this information to be reliable, but the accuracy and completeness of such information is not guaranteed. Each user should make their own test to determine the products suitability for the intended purpose/application and shall assume all risks and liabilities in connection therewith.